

Key Features

- 3rd generation LED technology for greater sustainability
- Maintenance free: 60,000-hour light source life and less power consumption
- 4,000 ANSI Lumens offering bright images in any environment
- 1080p Full HD resolution with HDR/HLG support to clearly present your ideas
- Ease of use: instant power on/off, H/V keystone, and LAN control



Product Description

The LS610HDH is ViewSonic's lamp-free high brightness 1080p projector for business and education. Adopting industry-leading 3rd generation LED technology, the LS610HDH delivers 4,000 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering the total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering a wider color gamut for bright, vivid images. Boasting 1080p Full HD resolution with HDR/HLG support, the projector provides radiant clarity helping you present your best whether in a meeting room, classroom, or any other environment. This projector also comes with instant power on/off for efficient use. With H/V keystone, 4 corner image adjustment and 360 tilt angle projection, the LS610HDH also allows for flexible setup. Moreover, its comprehensive LAN control enables multiple device management and is compatible with Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic's vController.







1. Zoom/Focus Ring 2. Front IR 3. Keypad 4. Top IR 5. Speaker 6. LAN Control 7. Audio In & Out 8. HDMI x 2 9. USB-A (5V/1.5A, Service) 10. RS232 Visit Us www.viewsonic.com

| SPECIFICATION | | OTHERS | |
|---------------------------------------------|-------------------------------------------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Native Resolution: | 1920x1080 | Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz |
| Brightness: | 4000 (ANSI Lumens) (ANSI Lumens) | Power Consumption: | (AC in) Normal: 330W |
| Brightness (Lumens): | 5000 | | Standby: <0.5W |
| Contrast Ratio: | 3000000:1 | Operating Temperature: | 0~40℃ |
| Display Color: | 1.07 Billion Colors | Carton: | Brown |
| Light Source Type: | LED | Net Weight: | 5.00kg |
| Light Source Life (hours) with Normal Mode: | 60000 | Gross Weight: Dimensions (WxDxH) with | 7.00kg 386x276x116mm |
| Lens: | F=1.6-1.75, f=19.16-23.02 | Adjustment Foot: | |
| Projection Offset: | 83%+/-9% | Packing Dimensions: OSD Language: | 490x376x268mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T- Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian. Total 24 languages |
| Throw Ratio: | 1.3-1.56 | | |
| Optical Zoom: | 1.2X | | |
| Digital Zoom: | 0.8x-2.0x | | |
| Image Size: | 30"-300" | | |
| Throw Distance: | 0.87-10.38m (100"@2.88m) | User Guide Language: | English, Simp.Chinese, Trad_Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese. Total 20 languages |
| Keystone: | H: +/- 40°, V: +/- 40° | | |
| Audible Noise (Normal): | 32dB | | |
| Audible Noise (Eco): | 27dB | | |
| Input Lag: | 16ms | STANDARD ACCESSORY | Total 20 languages |
| Resolution Support: | VGA(640 x 480) to 4K UHD (3840 x 2160) | Power Cord: | 1 |
| HDTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD | Remote Control: | 1 (w/ laser pointer) |
| Horizontal Frequency: | 15K-135KHz | QSG: | Yes |
| Vertical Scan Rate: | 23-120Hz | Warranty Card: | Yes (CN Only) |
| INPUT | | OPTIONAL ACCESSORY | |
| HDMI: | 2 (HDMI 2.0, HDCP 1.4/2.2) | Wall/Ceiling Mount: | PJ-WMK-007 |
| Audio-in (3.5mm): | 1 | | |
| OUTPUT | | | |
| Audio-out (3.5mm): | 1 | | |
| Speaker: | 10W | | |
| USB Type A (Power): | 1 (5V/1.5A) | | |
| CONTROL | | | |
| RS232 (DB 9-pin male): | 1 | | |
| RJ45 (LAN control): | 1 | | |
| USB Type A (Services): | 1 (share with USB A Output) | | |