

PROJECTOR



- 2nd generation laser phosphor ٠ technology with up to 30,000 hours lifespan
- 5,000 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen with lower cost-per-inch
- Installation flexibility: V lens shift, 1.6x optical zoom, H/V keystone
- Versatile application: 360° projection, portrait mode



Product Description

The Luminous Superior series is ViewSonic's lamp-free high brightness lineup for both commercial and educational spaces. The LS751HD adopts industry-leading 2nd generation laser phosphor technology and delivers 5,000 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering the total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering up to 300" large images with 1080p high resolution and vivid colors no matter if you're in a boardroom, lecture hall, or public space. The projector boasts high installation flexibility with vertical lens shift, 1.6x optical zoom, easy image adjustment with H/V keystone and 4 corner correction, and diverse applications with 360° projection and portrait mode. The LS751HD also comes with HDMI 2.0b, ensuring access to original 4K quality content with HDR/HLG supported.





SPECIFICATION		OTHERS	
Native Resolution:	1920x1080	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz
Brightness:	5000 (ANSI Lumens)	ronor cupply voltage.	(AC in)
Contrast Ratio:	300000:1	Power Consumption:	Normal: 245W Standby: <0.5W
Display Color:	1.07 Billion Colors	Operating Temperature:	0~40°C
Light Source Type:	Laser Phosphor	Carton:	Brown
Light Source Life (hours) with Normal Mode:	20000	Net Weight:	4.5kg
Light Source Life (hours) with		Gross Weight:	6.6kg
SuperEco Mode:	30000 (Eco)	Dimensions (WxDxH) with	337x265x131.5mm
Lens:	F=2.5-3.26, f=20.911-32.62mm	Adjustment Foot:	
Projection Offset:	136%+/-5%	Packing Dimensions:	496x195x387mm
Throw Ratio:	1.4~2.24	OSD Language:	English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Norwegian/Danish, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Farsi. Vietnamese, Indonesian, Romanian, Slovakian, total 27 languages
Optical Zoom:	1.6X		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	0.93-14.88m (100"@3.10m)		
Keystone:	H:+/-30°, V:+/-30°		English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai,
Lens Shift V. Range:	+0%, -18%	User Guide Language:	
Audible Noise (Normal):	32dB		
Audible Noise (Eco):	29dB		
Input Lag:	49.9ms	STANDARD ACCESSORY	Vietnamese, total 20 languages
Resolution Support:	VGA(640 x 480) to 4K UHD(3840 x 2160)	Power Cord:	1
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD	Remote Control: QSG:	1 Yes
Horizontal Frequency:	15K-102KHz		
Vertical Scan Rate:	23-120Hz		Yes (CN Only)
INPUT		OPTIONAL ACCESSORY Wall/Ceiling Mount:	PJ-WMK-007
HDMI:	2 (HDMI 2.0/ HDCP 2.2 HDMI 1.4/ HDCP 1.4)	Wancening Mount.	F 3- WWK-007
OUTPUT			
Audio-out (3.5mm):	1		
Speaker:	15W x2		
USB Type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		
USB Type A (Services):	1 (share with USB A Output)		