## Key Features

- 95% DCI-P3 & 100% sRGB wide color gamut
- Hardware color calibration
- Delta E < 2 color accuracy
- Pre-calibrated uniformity correction
- 21:9 aspect ratio



## Product Description

With an immersive curved screen and stunning WQHD+ 3840x1600 resolution, the ViewSonic VP3881a monitor elevates your viewing experience from flat to panoramic. With Pantone validated 95% DCI-P3 & 100% sRGB color coverage, and an amazing Delta E<2 value, this 4K monitor provides industry standard color accuracy to ensure superior results, while HDR10 compatibility delivers a wider dynamic range of vivid colors and richer contrast. Thanks to an expansive 38" frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. With a sleek and modern design, the VP3881a features a future-proof USB-C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming, and gaming. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

Visit Us www.viewsonic.com



DISPLAY Display Size (in.): Viewable Area (in.): Panel Type: Resolution: Resolution Type: Static Contrast Ratio: Dynamic Contrast Ratio:	38 37.5 IPS Technology 3840 x 1600 WQHD+ (Wide QHD+)	VIDEO INPUT Digital Sync: ERGONOMICS Height Adjust (mm): Swivel:	PCI-E - DisplayPort (v1.4), TMDS - HDMI (v2.0), Micro-Packet - Type C 130
Panel Type: Resolution: Resolution Type: Static Contrast Ratio:	IPS Technology 3840 x 1600	ERGONOMICS Height Adjust (mm):	130
Resolution: Resolution Type: Static Contrast Ratio:	3840 x 1600	Height Adjust (mm):	
Resolution Type: Static Contrast Ratio:			
Static Contrast Ratio:	WQHD+ (Wide QHD+)	Swivei.	120-
		Tilt (Forward/Back):	-1° / 21°
Dynamic Contrast Ratio:	1,000:1 (typ)	WEIGHT (IMPERIAL)	-1 /21
	20M:1	Net (lbs):	27.7
Light Source:	LED	Net Without Stand (lbs):	17.4
Brightness:	300 cd/m² (typ)	Gross (lbs):	41.8
Colors:	1.07B	WEIGHT (METRIC)	11.0
Color Space Support:	10 bit (8 bit + A-FRC)	Net (kg):	12.6
Aspect Ratio:	21:9	Net Without Stand (kg):	7.9
Response Time (Typical GTG):	5ms	Gross (kg):	18.9
Response Time (GTG w/OD):	5ms	DIMENSIONS (IMPERIAL) (W	/XHXD)
Viewing Angles:	178° horizontal, 178° vertical	Packaging (in.):	41.2 x 23.2 x 14.8
Backlight Life (Hours):	30000 Hrs (Min)	Physical (in.):	35.3 x 19.65~24.77 x 11.8
Curvature:	2300R	Physical Without Stand (in.):	35.3 x 15.7 x 4.1
Refresh Rate (Hz):	60	DIMENSIONS (METRIC) (WX	HXD)
Blue Light Filter:	Yes	Packaging (mm):	1046 x 590 x 375
Flicker-Free:	Yes	Physical (mm):	896 x 499.24~629.24 x 299
	Adobe RGB: 97% size / 86% coverage (Typ) DCI-P3: 96% size / 94% coverage	Physical Without Stand (mm):	896 x 398 x 103
		GENERAL	
Color Gamut:	(Typ) EBU: 129% size / 100% coverage (Typ) REC709: 131% size / 100% coverage (Typ) SMPTE-C: 141% size / 100% coverage (Typ) NTSC: 92% size (Typ)	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, MX-COC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, UKCA, CCC, China RoHS, China Energy Label, CECP VP3881A x1, 3-pin Plug (IEC C13 /
Pixel Size:	sRGB: 131% size / 100% coverage (Typ)  0.229 mm (H) x 0.229 mm (V)	PACKAGE CONTENTS:	CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2 Male-Male) x1, AC/DC Adapter x1,
Surface Treatment:	Anti-Glare, Hard Coating (3H)		Quick Start Guide x1
COMPATIBILITY PC Resolution (max):	3840x1600	Recycle/Disposal:	Please dispose of in accordance with
		,	local, state or federal laws.
Mac® Resolution (max): PC Operating System:	3840x1600 Windows 11 certified; macOS tested	Warranty:	*Warranty offered may differ from market to market
Mac® Resolution (min):	3840x1600	Power Management:	Energy Star standards, EPEAT
CONNECTOR  USB 3.2 Type A Down Stream:  USB 3.2 Type B Up Stream:  USB 3.2 Type C Up Stream;	2		
DisplayPort Alt mode : 3.5mm Audio Out:	1		
HDMI 2.0 (with HDCP 2.2):	2		
DisplayPort:	1		
Power in:	DC Socket (4 Pin)		
Ethernet LAN (RJ45):	1		
Internal Speakers:	5Watts x2		
POWER			
Eco Mode (Conserve):	36W		
Eco Mode (optimized):	41W		
Consumption (typical):	52W		
Consumption (max):	56W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS  Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5,		
On Screen Display:	Key 6 (power)  Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
	-g,		
OPERATING CONDITIONS	22°F to 104°F (0°C to 10°C)		
OPERATING CONDITIONS Temperature:	32°F to 104°F (0°C to 40°C)		
Temperature: Humidity (non-condensing):	20% to 90%		
Temperature: Humidity (non-condensing): WALL MOUNT			
Temperature: Humidity (non-condensing):	20% to 90%		
Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible:	20% to 90%		