Tech Specs

Technical Information

Number of Screens

1

Viewable Screen Size

23.8"

Panel Technology

In-plane Switching (IPS) Technology

Aspect Ratio

16:9

Horizontal Viewing Angle

178°

Mount Type

Panel Mount

HDCP Supported

Yes

Tilt Angle

-5° to 21°

Pivot Angle

+/-90°

Screen Size Class

24"

Screen Mode

WQHD

Response Time Details

• 8ms GTG

• 5ms GTG (Fast)

Pixel Pitch

0.2058 mm x 0.2058 mm

Vertical Viewing Angle

178°

Backlight Technology

LED Edgelight System

Maximum Adjustable Height

150 mm

Swivel Angle

-45° to 45°

Features

Narrow Bezel

Mercury-free

Arsenic-free Glass

PVC Free

• BFR Free

Stand Lock

Cable Lock Slot

Security Lock

- Anti-glare
- Eye Comfort Technology
- sRGB

Horizontal Frequency

30 kHz to 150 kHz

Vertical Frequency

48 Hz to 100 Hz

Adjustable Stand

Yes

Stand Adjustments

- Swivel
- Height
- Pivot
- Tilt

Stand Included

Yes

Glass Hardness

3H

Operation Hours

8 Hours/5 Days

Video

Maximum Resolution

2560 x 1440

Standard Refresh Rate

100 Hz

Color Supported

16.7 Million Colors

Native Contrast Ratio

1,500:1

Brightness

350 cd/m² (typical)

Color Gamut

99% sRGB (CIE 1931)

Maximum Preset Resolution

2560 x 1440 at 100Hz

Pixel Per Inch (PPI)

123

Interfaces/Ports

Connectivity

Video port

- 1 HDMI port (HDCP 1.4) (Supports up to QHD 2560 x 1440 100Hz TMDS as per specified in HDMI 2.1)
- 1 Display Port 1.4 (HDCP1.4)(Support up to 2560 x 1440 100Hz)
- 1 DisplayPort (out) port with MST (HDCP 1.4)

USB port

- 1 USB-C 5Gbps upstream port (DisplayPort 1.4 Alternate mode, Power Delivery up to 90W)
- 1 USB-C 5Gbps downstream port
- 3 USB 5Gbps Type-A downstream ports
 Ethernet port
- 1 RJ45 Ethernet port, 1GbE

USB Type-C (Power Delivery)

90 W

Built-in Devices

Built-in Devices

NA

Environmental Conditions

Operating Temperature Range

32°F (0°C) to 104°F (40°C)

Operating Humidity Range

10% to 80% (Non-condensing)

Maximum Operating Altitude

16400 ft

Non-operating Temperature Range

-4°F (-20°C) to 140°F (60°C)

Non-operating Humidity Range

5% to 90% (Non-condensing)

Maximum Non-operating Altitude

40000 ft

Power Description

Input Voltage Range

100V AC to 240V AC

Standby Power Consumption

0.3 W

Frequency

• 50 Hz

• 60 Hz

Voltage Current

2.0 A

Operating Power Consumption

16.5 W

Off-Mode Power Consumption

0.3 W

Maximum Power Consumption

185 W

Physical Characteristics

VESA Mount Compatible

Yes

VESA Mount Standard

100 x 100

Height

12.41 in.

Width

21.21 in.

Depth

1.96 in.

Height with Stand

19.55 in.

Width with Stand

21.21 in.

Depth with Stand

1.96 in.

Compressed Height with Stand

14.33 in.

Extended Height with Stand

19.55 in.

Bezel Width (Top)

0.23 in.

Bezel Width (Bottom)

0.51 in.

Bezel Width (Left)

0.23 in.

Bezel Width (Right)

0.23 in.

Weight (Approximate)

8,33 lb

Stand Height

16.17 in.

Stand Width

9.83 in.

Stand Depth

7.15 in.

Weight with Stand (Approximate)

12.37 lb

Miscellaneous

Package Contents

- Monitor
- Stand
- QR Card
- Safety, Environmental, and Regulatory Information

Cables Included

- Power cable
- 1 DisplayPort to DisplayPort 1.4 cable 1.80 m
- 1 USB-C to C 10Gbps, 100W cable 1.00
 m

Cable tie

 1 USB Type-C to Type-A 5Gbps cable -1.80 m

Energy Star

Yes

Country of Origin

China/Thailand

TCO Certified

Yes

Dell Display Manager Compatibility

Yes

Remote Asset Management

DDPM

Cable Type Included

- Power cable
- 1 x DisplayPort to DisplayPort 1.4 cable 1.80 m
- 1 x USB-C to C 10Gbps, 100W cable -1.00 m
- 1 x USB Type-C to Type-A 5Gbps cable -1.80 m

Environmentally Friendly

Yes

Environmental Certification

- TCO Certified Edge
- Electronic Product Environmental Assessment Tool Climate+ (EPEAT Climate+)
- Electronic Product Environmental Assessment Tool Gold (EPEAT Gold)

Energy Efficiency Certification

ENERGY STAR 8.0

Energy Efficiency Compliance

Energy-related Products Directive Lot 5 (ErP Lot 5)

Environmental Compliance

Restriction of Hazardous Substances (RoHS)

Warranty

Limited Warranty

3 Years

Additional Warranty Information

3 Years Limited Hardware and Advanced Exchanged Service