

# Tech Specs

## Technical Information

**Diagonal Viewing Size**  
23.8"

**Panel Type**  
In-Plane Switching (IPS) technology

**Maximum Preset Resolution**  
1920 x 1080

**Viewing Angle**  
178° vertical / 178° horizontal

**Pixel Per Inch (PPI)**  
92.53

**Aspect Ratio**  
16:9

**Brightness**  
250 cd/m<sup>2</sup> (typical)

**Color Support**  
Up to 16.7 million colors

**TÜV Eye Comfort**  
Yes, 4-Star

**Connectivity**

- 1x HDMI 1.4 (HDCP 1.4) (Supports up to FHD 1920 x 1080 100Hz TMDS as per specified in HDMI 1.4)
- 1x DP 1.4 (HDCP 1.4)
- 1x DP-out (1.4) with MST (HDCP 1.4)
- 1x RJ45 Ethernet port, 1GbE
- 1x USB 3.2 Gen1 Type-C upstream (Alt. mode with DP1.4) with up to 90W PD
- 3x USB 3.2 Gen1 Type-A downstream
- 1x USB 3.2 Gen1 Type-C downstream with up to 15W PD (data only)

**USB Power Delivery**  
Yes, up to 90W via USB-C upstream (Alt. mode with DP1.4) port, and up to 15W via USB-C downstream port

**Height**  
Up to 150 mm (5.9")

**Swivel**  
-45°/+45°

**Daisy Chain Availability**  
Yes

**Dell Display Manager Compatibility**  
Yes with Easy Arrange

**Voltage Required**  
100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (typ)

**Audio Output**  
Optional soundbar (sold separately)

**Preset Display Area (H x V)**  
527.04 mm x 296.46 mm (20.75" x 11.67")  
Area: 156,246.28 mm<sup>2</sup> (242.18 inches<sup>2</sup>)

**Display Screen Coating**  
Anti-glare with 3H hardness

**Refresh rate**  
100 Hz

**Pixel Pitch**  
0.2745 mm x 0.2745 mm

**Contrast Ratio**  
1,500: 1 (typical)

**Backlight Technology**  
LED edgelight system

**Response Time**  
5ms gray-to-gray (Fast mode)  
8ms gray-to-gray (Normal mode)

**Color Gamut**  
99% sRGB

**Flicker Free**  
Yes

**Built-in Speaker**  
No

**Adjustability**  
Height, Tilt, Swivel, Pivot

**Tilt**  
-5°/+21°

**Pivot**  
-90°/+90°

**Dell Power Button Sync**  
Yes, via USB Type-C upstream port

**Remote Asset Management**  
Yes

**Power Consumption (Operational) (typical)**  
0.3 W (Off mode)  
0.3 W (Standby mode)  
1.0 W (Networked Standby mode)  
13.9 W (On mode)  
180 W (Max)  
15.2 W (Pon)  
49.8 kWh (TEC)

**Security**  
Security-lock slot (based on Kensington Security Slot™)

**Compliant Standards**

ENERGY STAR certified monitor  
EPEAT GOLD  
EPEAT Climate+  
TCO Certified Displays  
TCO Certified Edge  
RoHS-compliant  
BFR / PVC free monitor (excluding external cables)  
Arsenic-free glass and mercury-free (panel only)

**Temperature Range**

Operating: 0°C ~ 40°C (32°F ~ 104°F)  
Non-operating: -20° ~ 60°C (-4° ~ 140°F)

**Altitude**

Operating: 5,000 m (16,404 ft) max  
Non-operating: 12,192 m (40,000 ft) max

**Cables Included**

- 1x Power cord
- 1x DP-to-DP cable, 1.8m
- 1x USB 3.2 Gen2 Type C-to-C cable, 1.0m

**Flat Panel Mount Interface**

VESA (100 mm x 100mm)

**Humidity Range**

Operating: 10% ~ 80% (non-condensing)  
Non-operating: 5% ~ 90% (non-condensing)

**What's Included**

- 1x Monitor panel
- 1x Stand riser and base
- 1x Cable tie
- 1x Quick setup guide
- 1x Safety, Environmental, and Regulatory Information

---

**Physical Characteristics**

**Height with stand (Compressed ~ Extended)**

14.33" ~ 19.55"

**Depth with stand**

7.16"

**Width without stand**

21.21"

**Weight (panel only - for VESA mount)**

8.13 lbs

**Width with stand**

21.21"

**Height without stand**

12.37"

**Depth without stand**

1.97"

**Weight (with packaging)**

15.96 lbs

---

**Warranty**

**Specifications - Service / Support Details**

3 Year Limited Hardware Warranty with Advanced Exchange Service and Premium Panel Exchange