

Tech Specs

General

| | |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Display Type LED-backlit LCD monitor / TFT active matrix | Diagonal Size 31.5" |
| Curved Screen Yes (1800R) | Adaptive-Sync Technology AMD FreeSync™ Premium Technology |
| Panel Type VA | Aspect Ratio 16:9 |
| Native Resolution QHD 2560 x 1440 (DisplayPort: 165 Hz, HDMI: 144 Hz) | Pixel Pitch 0.2724 mm |
| Pixel Per Inch 93 | Brightness 350 cd/m² |
| Contrast Ratio 3000:1 / 3000:1 (dynamic) | Color Support 16.8 million colors |
| Response Time 2 ms (gray-to-gray); 1 ms (MPRT) | Horizontal Viewing Angle 178° |
| Vertical Viewing Angle 178° | Screen Coating Anti-glare 3H hardness |
| Backlight Technology LED backlight | Features LED edgelight system, 99% sRGB color gamut |
| Built-in Speaker No | Dimensions (WxDxH) 27.9 in x 9.4 in x 18 in - with stand (lowest position) |

Connectivity

Interfaces

- 2 x HDMI (HDCP 2.2)
- DisplayPort (DisplayPort 1.2 mode, HDCP 2.2)
- Audio line-out (mini-jack)

Mechanical

Display Position Adjustments
Height, tilt

Tilt Angle
-5°/+21°

Height Adjustment
3.9 in

VESA Mounting Interface
100 x 100 mm

Miscellaneous

Features
VESA interface support

Cables Included

- 1 x HDMI cable
- 1 x DisplayPort cable - DisplayPort to DisplayPort

Compliant Standards
DisplayPort 1.2, HDCP 2.2

Power

Input Voltage
AC 100-240 V (50/60 Hz)

Power Consumption (On mode)
26 W

Power Consumption Stand by

Power Consumption (Off Mode)

0.3 Watt

0.25 Watt

On / Off Switch

Yes

Dimensions & Weight

Dimensions & Weight Details

- With stand (lowest position) - width: 27.9 in - depth: 9.4 in - height: 18 in
- Without stand - width: 27.9 in - depth: 3.2 in - height: 16.7 in - weight: 16.4 lbs

Dimensions & Weight (Shipping)

Shipping Weight

31.97 lbs

Manufacturer Warranty

Bundled Services

3-Year Advanced Exchange Service and Premium Panel Exchange

Environmental Parameters

Min Operating Temperature

32 °F

Max Operating Temperature

104 °F

Humidity Range Operating

10 - 80% (non-condensing)