

Tech Specs

Technical Information

Diagonal Viewing Size 27"	Preset Display Area (H x V) 596.74 mm x 335.66 mm 23.49" x 13.22" 200,301.74 mm ² (310.47 inches ²)
Panel Type IPS Black Technology	Display Screen Coating Anti-Glare with 3H hardness
Maximum Preset Resolution QHD 2560 x 1440 at 120 Hz	Viewing Angle 178° vertical / 178° horizontal
Pixel Pitch 0.2331 mm x 0.2331 mm	Pixel Per Inch (PPI) 108.97
Contrast Ratio 2000 to 1 (typical)	Aspect Ratio 16:9
Backlight Technology LED Edgelight System	Brightness 350 cd/m ² (typical)
Response Time 8 ms (Normal) 5 ms (Fast)	HDR Ready No
Ambient Light Sensor Yes, auto brightness and color temperature adjustmemt	color support 1.07 billion colors
Color Gamut 100% sRGB, 100% BT.709, 98% Display P3, 98% DCI-P3, Delta E < 2 (average) (sRGB, BT.709, Display P3, DCI-P3)	Interfaces <ul style="list-style-type: none">• 1 x DisplayPort 1.4 (DRR for Microsoft Windows) (Supports 2 x QHD 120Hz 8 bit)• 1 x DisplayPort 1.4 (Out)• 1 x HDMI (HDCP 1.4)(Supports up to QHD 2560 x 1440 120Hz TMDS, VRR as per specified in HDMI 2.1)• 1 x Thunderbolt™ 4 downstream port (15W) for daisy chaining• 1 x Thunderbolt™ 4 upstream port (Video + Data). Alternate mode with DisplayPort 1.4, power delivery up to 90W.• 1 x USB-Type C upstream port (data only) (SuperSpeed USB 10 Gbps, USB 3.2 Gen 2• 3 x USB Type-A downstream port (SuperSpeed USB 10 Gbps, USB 3.2 Gen 2)• 1 x Audio line out• 1 x RJ45 Ethernet port, 2.5GbE (2.5G)• 1 x USB Type-A downstream port (SuperSpeed USB 10 Gbps, USB 3.2 Gen 2) with BC1.2 power charging• 1 x USB Type-C downstream port (SuperSpeed USB 10 Gbps, USB 3.2 Gen 2) with power charging (15W)
Adjustability Height, Tilt, Swivel, Pivot	Height adjustable 150 mm
Tilt -5°/+21°	Swivel -45°/+45°
Pivot -90°/+90°	PbP / PiP Yes
Keyboard, Video and Mouse (KVM) Yes	Daisy Chain Availability Yes
Audio Output 1 x Audio line-out	Built-in Speaker No
Security Security lock slot (cable lock sold separately) Anti-theft stand lock slot (to lock stand to monitor using screw)	Compliant Standards ENERGY STAR certified Monitor. EPEAT registered where applicable. EPEAT registration varies by country. See https://www.epeat.net for registration status by country. TCO Certified & TCO Certified Edge.

	RoHS Compliant. BFR/PVC Free monitor (excluding external cables). Arsenic-Free glass and Mercury-Free for the panel only
Flat Panel Mount Interface VESA mounting holes (100 mm x 100 mm - behind attached VESA Cover)	What's Included Monitor, Stand Riser, Stand Base, Quick setup guide, Safety, Environmental and Regulatory Information, Factory calibration report
Cables Included 1 x Power cable 1 x DisplayPort 1.4 cable - 1.8 m 1 x USB Type-A to USB Type-C Gen 2 cable - 1 m 1 x Thunderbolt™ 4 cable - 1 m	Voltage Required 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2.65 A (typical)
Power Consumption (On mode) 24.4 W	Power Consumption (Max) 225 W
Power Consumption Stand by 0.5 W	Power Consumption (Off Mode) 0.3 W
Networked standby mode 1.5 W	Dell Display Manager Compatibility Yes , Easy Arrange, Other key features
Temperature Range Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F)	Humidity Range Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing)
Altitude Operating: 5000 m (16404 ft) max Non-Operating: 12192 (40000 ft) max	

Physical Characteristics

Height with stand (Compressed ~ Extended) 15.18" ~ 21.09	Width with stand 24.10"
Depth with stand 7.57"	Height without stand 13.88"
Width without stand 24.10"	Depth without stand 1.97"
Weight (panel only - for VESA mount) 11.53 lb	Weight (with stand assembly and cables) 16.25 lb
Weight (with packaging) 22.51 lb	

Warranty

Specifications - Service / Support Details
3-Year Advanced Exchange Service and Premium Panel Exchange