M C2510

MAIN SPECIFICATIONS

GENERAL	
Warm-up time	25 seconds
First copy speed: BW	7.5 seconds
First copy speed: full colour	9.6 seconds
Continuous output speed	25 ppm
Memory: standard	2 GB
Storage: standard	64 GB
ARDF capacity	50 sheets
Weight	63.6 kg
Dimensions: W x D x H	585 x 670 x 752 mm
Power source	220 - 240 V, 50 - 60 Hz
COPIER	
Multiple copying	Up to 999 copies
Resolution	Scanning: : 600 x 600 dpi Printing: : 600 dpi, 1200 dpi
Zoom	From 25% to 400% in 1% steps
PRINTER	
First print speed: B/W	8 seconds
First print speed: full colour	10 seconds
CPU	ARM CortexA7-Dual 1.0GHz
Printer language: standard	PCL6/PS3
Print resolution	Maximum: 1,200 x 1,200 dpi/1bit
Network interface: standard	Ethernet (RJ-45 network port: 10Base-T/100Base-TX/1000Base-T) USB 2.0 Host I/F(Type A:2 Port) USB 3.0 Device I/F(Type B:1 Port)
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac)
Mobile printing capability	Apple AirPrint Mopria®
Windows® environments	PCL6: Windows® 10/11, Windows Server® 2012 or later PS3: Windows® 10/11, Windows Server® 2012 or later TWAIN: Windows® 10/11, Windows Server® 2012 or later
Mac OS environments	macOS v11 or later
UNIX environments	Red Hat Enterprise Linux 7 (x64, 7.3–7.9), 8, 9 Ubuntu 18.04/20.04/22.04/24.04 LTS (x64) BOSS 9/10 OpenSUSE Leap 15.6 (x64) UOS Desktop V20, Kylin Desktop V10
Chrome OS environments	Chrome OS 97 or later
SCANNER	
Scanning speed: ARDF (A4 LEF, B&W full colour)	50 ipm (200dpi)
Resolution: maximum	600 dpi
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Multi page TIFF, Multi page PDF
Scan modes	E-mail, USB, Folder (SMB, FTP), Cloud
PAPER HANDLING	
Recommended paper size	Standard paper tray(s): A3, B4, A4-R, A4, B5-R, B5, A5-R, FOLIO, 8K, 16K, 16K-R, LD, LG, LT, LT-R, ST-R, COMP, 13"LG , 8.5"x8.5", Custom size paper: Width: 100 mm - 297 mm, Length: 148 mm - 432 mm Optional paper tray(s) : Paper Feed Unit PB3380/Paper Feed Unit PB3390 (A3, B4, A4-R, A4, B5-R, B5, A5-R, FOLIO, 8K, 16K, 16K-R, LD, LG, LT, LT-R, ST-R, COMP, 13"LG , 8.5"x8.5"), Paper Feed Unit PB3400 (A4, LT) Bypass tray: A3, B4, A4-R, A4, B5-R, B5, A5-R, FOLIO, 8K, 16K, 16K-R, LD, LG, LT, LT-R, ST-R, COMP, 13"LG , 8.5"x8.5", Custom Size paper: Width: 100 mm - 297 mm, Length: 148 mm - 432 mm
Paper input: standard	350 sheets
Paper input: maximum	2,900 sheets
Paper output: standard	550 sheets
Paper weight: standard	60 - 163 g/m²
Paper weight: trays	60 - 163 g/m²
Paper weight: bypass	60 - 209 g/m²
Paper weight: duplex	60 - 163 g/m²
Paper types	Plain paper, Envelope, Label paper, OHP, Thick paper, Thin paper

M C2510

MAIN SPECIFICATIONS

ECOLOGY

Power consumption: max.	< 2,000 W
Power consumption operation: B&W	334 W
Power consumption operation: Full colour	348 W
Power consumption: ready	91.8 W
Power consumption: sleep	0.37 W
TEC*	0.29 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.2 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 550-sheet paper tray, 2x 550-sheet paper tray, 2,000-sheet Large capacity tray

OTHER OPTIONS

Low cabinet, NFC Card Reader Option Type M66, IEEE 802.11 Interface Unit Type M47

CONSUMABLES

Toner (black)	15,000 prints
Toner (cyan/magenta/yellow)	10,000 prints
Consumable yield based on 5% coverage/A4	2p/j

For availability of models, options and software, please consult your local supplier.

Ricoh Europe (Netherlands) B.V.
John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands

+31 (0)20 5774111

ricoh-europe.com

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2026 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.