


NVR

16CH NVR

16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P HD NVR



TD-3316H2-B2-B

- 4K Output
- 16MP
- DDNS
- Network
- PTZ
- Audio
- MIC
- Mobile
- CMS
- USB
- Mouse
- E-mail
- STD
- FR
- VCA

This product supports 16 CH 16MP / 12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280x1024/960P / 720P high definition IP input, which adopts the advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

This product supports 16CH IPC input , simultaneous 16CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



en.tvt.net.cn

For more information, please visit our website

SPECIFICATIONS



Model		TD-3316H2-B2-B
System	OS	Embedded Linux
Video	Compression	H.265S/H.265+/H.265/H.264
	IP Video Input	16CH IPC input
	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
	Incoming/Outgoing Bandwidth	192Mbps/192Mbps *When the AI function of the IPC is enabled, the actual incoming bandwidth(max.bitrate) is more than the set value in the NVR.
	Output	HDMI×1 : 3840 × 2160/1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA can be set to output the same or different video source with HDMI
	Multi-screen Display	Main output:1/4/6/8/9/13/16 (live view) AUX output:1/4/6/8/9 (live view) AI mode: max 16CH (HDMI and VGA output the same video source, AI by device, face comparison and picture comparison supported) Non-AI mode (default mode): max 25CH (VGA can be set to output the same or different video source with HDMI, AI by device, face comparison and picture comparison not supported)
Audio	Network Input	16 CH IPC audio input
	2-way Audio	RCA × 1
	Local Output	RCA × 1
	Compression	G.711(U/A)
Record	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
	Frame Rate	NTSC: 30fps; PAL: 25fps
Playback	Simultaneous Playback	Max 16CH
	Search	Time slice / time / event / tag / smart search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Decoding Capability	Live View/ Playback	Non-AI Mode:1×16MP@30fps/4×8MP@30fps/9×3MP@30fps/16×2MP@30fps AI Mode: 1×16MP@30fps/4×5MP@30fps/9×2MP@30fps/16×720P@30fps
Alarm	Mode	Manual, sensor, motion, exception, smart events, etc.
	Input	8 CH local alarm input
	Output	4 CH
	Triggering	Record, snap, preset, e-mail, etc.
Face	Face Detection Performance (AI by IPC)	16CH
	Face Detection Performance (AI by Device)	Picture comparison disabled: 2 CH(2MP) or 1CH (4MP) Picture comparison enabled: 1CH(2MP) or 1CH (4MP)
	Face Match Performance	Picture comparison disabled: 6 CH Picture comparison enabled: 3 CH
	Comparison Capability	18 pictures / second
	Face Picture Database	32 libraries 10000 Face Pictures
	Face Picture Search	Search by picture is supported
	Database Management	Add, modify, delete and search face pictures
	Face Picture Adding	Add face pictures through APP, WEB and external import
	Face Picture Comparison	Support allow list, block list and stranger match alarm
	Track	Track display on a map
	Statistical Graph of Information	Bar graph
Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period	

Perimeter Protection	Human/Vehicle Classification (AI by IPC)	16 CH
	Human/Vehicle Classification (AI by Device)	Picture comparison disabled: 2 CH(2MP) or 1CH (4MP) Picture comparison enabled: 1CH(2MP) or 1CH (4MP)
Video Metadata	Human/Vehicle Attribute Analysis	Yes (AI by IPC)
Other Functions	Fisheye	Supports fisheye camera access
	Plate Recognition (AI by IPC)	Yes
Network	Interface	RJ 45 1000 Mbps × 2
	Protocol	TCP/IP, IPv4, IPv6, UDP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, HTTP, FTP, SMTP, HTTPS, 802.1x, RTSP, RTP, RTCP, WebSocket, SNMP, IGMP, ONVIF
	Client Connection	Max. 64 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA × 2, max 10T for each HDD
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
External Interface	RS 485	Yes (full-duplex), connect to PTZ or keyboard
	USB	USB 3.0 × 1 ; USB 2.0 × 2
	Remote Controller	Optional
Others	Power Supply	DC12V/4A
	Consumption	≤ 20W (without HDD)
	Certificate	CE, FCC
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE
	Dimensions(mm)	380 × 268 × 48.1 (W × D × H)
Working Environment	-10 ~ 50 °C, 10% ~ 90% humidity	

FEATURES

- Support 16 CH 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF IPC Input
- H.265S/H.265+/H.265/H.264
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event, tag and smart search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Support license plate recognition
- Support POS information overlay on live view and playback
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

DIMENSIONS



REAR PANEL

