

Key Features


- Built-in Full HD webcam and microphone
- Adjustable vertical
 angles for greater frame control
- Webcam slide cover ensures total security and privacy
- Ergonomic flexibility with quick release stand
- Minimized Total Cost of Ownership



Product Description

The ViewSonic VG2740V is a 27" Full HD video conferencing monitor designed to deliver out-of-the-box video conferencing and high-quality live streaming capability. The built-in Full HD webcam allows you to easily adjust the vertical angles to better frame yourself during VC calls and create more engaging content through varied camera angles, while the easy-to-use cover slide ensures total privacy and security when not in use. Providing the full spectrum of ergonomic flexibility, the VG2740V can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow, and the exceptional inbuilt microphones and dual 2W speakers ensure you can hear and be heard with absolute clarity and professionalism. Combined with the vDisplay Manager productivity software for efficient multi-tasking and streamlined on-screen display control, the VG2740V is the complete solution for anybody looking for a professional live streaming or video communication experience.







DISPLAY		VIDEO INPUT	
Display Size (in.):	27	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Viewable Area (in.):	27		Separate/Composite/SOG - RGB
Panel Type:	IPS Technology	Analog Sync:	Analog
Resolution:	1920 x 1080	ERGONOMICS	
Resolution Type:	FHD (Full HD)	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	80M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	300 cd/m ² (typ)	WEIGHT (IMPERIAL)	
Brightness (PCS):	300 cd/m ² (typ)	Net (lbs):	15.9
Colors:	16.7M	Net Without Stand (lbs):	10.6
Color Space Support:	8 bit (6 bit + Hi-FRC)	Gross (lbs):	22.5
Aspect Ratio:	16:9	WEIGHT (METRIC)	7.0
Response Time (Typical GTG):	5ms	Net (kg):	7.2
Response Time (GTG w/OD):	5ms	Net Without Stand (kg):	4.8
Viewing Angles:	178° horizontal, 178° vertical	Gross (kg):	
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W Packaging (in.):	27.2 x 17.9 x 8.6
Curvature:	Flat	Physical (in.):	24.4 x 16.76~21.93 x 8.1
Refresh Rate (Hz):	60		
Blue Light Filter:	Yes	Physical Without Stand (in.):	24.4 x 15.3 x 2.1
Flicker-Free:	Yes	DIMENSIONS (METRIC) (WXH	
	Adobe RGB: 76% size / 74%	Packaging (mm):	692 x 455 x 218
Color Gamut:	coverage (Typ) NTSC: 72% size (Typ) sRGB: 102% size / 95% coverage	Physical (mm):	621 x 425.64~557.04 x 206
	(Тур)	Physical Without Stand (mm):	621 x 389 x 55
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	GENERAL	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC,
COMPATIBILITY			
PC Resolution (max):	1920x1080		UkrSEPRO, UKCA, RCM, GEMS
Mac® Resolution (max):	1920x1080	PACKAGE CONTENTS:	VG2740V x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2; Male- Male) x1, Audio Cable (Male-Male) x1, Quick Start Guide x1
PC Operating System:	Windows 10/11 certified; macOS tested		
Mac® Resolution (min):	1920x1080	Popula/Disposal:	Please dispose of in accordance with
CONNECTOR VGA:	1	Recycle/Disposal:	local, state or federal laws.
USB 3.2 Type A Down Stream:	3	Warranty:	*Warranty offered may differ from market to market
USB 3.2 Type B Up Stream:	1	Power Management:	Energy Star standards, EPEAT
3.5mm Audio In:	1	, i i i i i i i i i i i i i i i i i i i	
	1		
3.5mm Audio Out: HDMI 1.4:	1		
DisplayPort: Power in:	1 2 pin Seeket (IEC C14 / CEE22)		
AUDIO	3-pin Socket (IEC C14 / CEE22)		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	16.6W		
Eco Mode (optimized):	20.77W		
Consumption (typical):	26.14W		
Consumption (max):	32.5W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:			
ADDITIONAL HARDWARE	Internal Power Supply		
	1		
Kensington Lock Slot: Webcam:			
	2.0M pixel Yes		
Cable Organization:			
Microphone:	Yes		
CONTROLS			
	Key 1 (velume dewn) Key 2 Key 2		
Physical Controls:	Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
Physical Controls: On Screen Display:	Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
On Screen Display:	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust,		
On Screen Display:	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing):	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing):	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible:	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90%		
On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible:	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90% 100 x 100 mm RGB Analog: 24 ~ 82KHz, HDMI (v1.4): 15 ~ 82KHz, DisplayPort		
On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing): WALL MOUNT VESA Compatible: INPUT SIGNAL	Key 4, Key 5, Key 6 (power) Input Select, Audio/Mic, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90% 100 x 100 mm RGB Analog: 24 ~ 82KHz, HDMI		