

Acer X1528i data projector Standard throw projector 4500 ANSI lumens DLP 1080p (1920x1080) 3D White


Brand : Acer Product code: MR.JU711.001

Product name: X1528i



Acer X1528i. Projector brightness: 4500 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Laser, Lamp power: 245 W, Lamps quantity: 1 lamp(s). Focal length range: 15.84 - 17.44 mm, Throw ratio: 1.5 - 1.66. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 1920 x 1200 (WUXGA). Projection modes: Ceiling, Front, Rear

Projector		Ports & interfaces	
Projection distance Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colors Keystone correction, vertical Horizontal synchronization (min) Horizontal synchronization (max) Vertical synchronization (max)	1 - 10 m 4500 ANSI lumens DLP 1080p (1920x1080) 10000:1 16:9 1.07 billion colors -40 - 40° 15 kHz 100 kHz 0.024 kHz 0.12 kHz	Composite video in * AC (power) in	1
		Network	
		Wi-Fi * Miracast	1
		Features	
		Projection modes	Ceiling, Front, Rear
		Multimedia	
		Built-in speaker(s) * RMS rated power Number of built-in speakers	√ 3 W 1
Light source		Design	
Light source type * Lamp power Lamps quantity	Laser 245 W 1 lamp(s)	Product type * Product color * Placement	Standard throw projector White Ceiling
Lens system		Display	
Focal length range Zoom capability	15.84 - 17.44 mm ✓	Built-in display *	×
Throw ratio	1.5 - 1.66	Power	
Video Analog signal format system * Full HD *	NTSC, PAL, SECAM ✓	Power source * Power consumption (typical) * Power consumption (standby) * AC input voltage	AC 290 W 0.5 W 120 - 230 V
3D * Supported graphics resolutions	√ 1920 x 1200 (WUXGA)	Supplier features	
Ports & interfaces	2020 X 2200 (Noxery	Harmonized System (HS) code	85286200
USB 2.0 ports quantity *	1	Operational conditions	
Audio (L/R) in * Audio (L/R) out PC in (D-Sub) VGA (D-Sub) ports quantity *	1 1 •• 1	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 0 - 80%
		Weight & dimensions	
		Width Depth Height Weight *	313 mm 240 mm 113.7 mm 2.9 kg
		Packaging content	
		Handheld remote control * Batteries included 3D glasses included Cables included	✓ ✓ X AC, VGA



4710886378006

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.